

Umwälzpumpen

Guss - und Edelstahl

- Normalsaugende Umwälzpumpen.

Pumpentyp	P ₂ [kW]	Spannung		Werkstoff		Q _{max.} [l/min.]	H _{max.} [m]	Anschluss Saug / Druck [Zoll]		
		1x230V	3x400V	Gehäuse / Laufrad						
	CPm100	0,25	X	--	Guss	AISI 304	60	16	G 1" IG	G 1" IG
	CPm130	0,37	X	X	Guss	AISI 304	80	23	G 1" IG	G 1" IG
	CPm158	0,75	X	--	Guss	AISI 304	90	36	G 1" IG	G 1" IG
	CPm132A	0,60	X	--	Guss	AISI 304	120	23	G 1" IG	G 1" IG
	ZM50	0,55	X	--	Guss	Kunststoff	114	22	G 1" IG	G 1" IG
	ZM100	0,75	X	--	Guss	Kunststoff	110	31	G 1" IG	G 1" IG
	PCC1100	0,75	X	--	Guss	Bronze	120	28	G 1" IG	G 1" IG
	NGA1B*	0,55	X	--	Guss	AISI 316	330	18	G 1½" IG	G 1½" IG
	NGA1A*	0,75	X	X	Guss	AISI 316	350	20	G 1½" IG	G 1½" IG
	PRO-NGA1A*	0,75	X	X	INOX 316	AISI 316	350	20	G 1½" IG	G 1½" IG
	ZP150	1,1	X	--	Guss	Bronze	450	22	G 2" IG	G 2" IG
	ZP300	2,2	--	X	Guss	Bronze	600	34	G 2" IG	G 2" IG
	HF20A	4	--	X	Guss	Bronze	1800	19	G 4" IG	G 4" IG

* offenes Laufrad