

Unloaderventile

Modell	Fördermenge max. l/min.	Druck max. bar
Unloader Ventile Standardausführung		
ULA150H	25,0	150
ULA201H	30,0	210
UL180/100 (H,F)	30,0	100
UL180/200 (H,F)	30,0	210
UL180/250 (H,F)	30,0	250
UL180/300 (H,F)	30,0	300
UL221/100 (H)	50,0	100
UL221/140 (H)	50,0	140
UL221/200 (H)	50,0	210
UL262/1 (H)	135,0	120
UL262/2 (H)	100,0	280
UL262/3 (H)	135,0	40
UL300/1 (H)	225,0	110
UL300/2 (H)	120,0	220
UL300/3 (H)	60,0	400
UL300/4 (H)	225,0	80
UL500/11H	250,0	150
UL500/11-D25	250,0	180
UL500/32H	100,0	500
UL500/11P	250,0	150
UL500/11P-D25	250,0	180
UL500/32P	100,0	500
UL50/500	50,0	500
UL50/500Dr	50,0	500
UL50/1000	50,0	1000

Modell	Fördermenge max. l/min.	Druck max. bar
Unloader Ventile mit Sonderdichtungen		
UL180/100V (R)	30,0	100
UL180/200V (H)	30,0	210
UL180/250V (R)	30,0	250
UL180/300V (R)	30,0	300
UL262/1V	135,0	120
UL262/2V	100,0	280
UL500/11HLF	250,0	100
Unloader Ventile in R-Ausführung		
UL181/150R	80,0	150
UL181/280R	80,0	280
UL181/400R	80,0	400
UL262/1RV	135,0	120
UL262/2RV	100,0	280
UL262/1R (H)	135,0	120
UL262/2R (H)	100,0	280
UL500/11HR	250,0	150
UL500/11PR	250,0	150
UL500/11PR-D25	250,0	180
UL500/32PR	100,0	500
UL500/32HR	100,0	500

